FUZRR

FR200 Series Clamp Digital Multimeter

Torch Build In Functions As Measuring Assistance



FUZRR®

MAKE THE BEST TESTING INSTRUMENT!

Why choose us!



VS



FR204E		204+
60.00A/600A	DC Current (A)	60.00A/600A
60.00A/600A	AC Current (A)	60.00A/600A
600mV/6V/60V/600V	DC Voltage (V)	600mV/6V/60V/600V
6V/60V/600V	AC Voltage (V)	6V/60V/600V
6V/60V/600V	LowZ AC Voltage (V)	-
1kHz	ACV/Bandwidth (Hz)	400Hz
10Hz~60kHz	Frequency (ACV Hz)	10Hz~60kHz
600Ω/6KΩ/60KΩ/600KΩ 6MΩ/60MΩ	Resistance (Ω)	600Ω/6KΩ/60KΩ/600KΩ 6MΩ/60MΩ
60nF~600n~600uF 6000uF/60000uF	Capacitance(F)	60nF~600n~600uF 6000uF/60000uF
(-50°C~1000°C)	Temperature (℃)	(-40°C~1000°C)
(-58°F~1832°F)	Temperature (°F)	(-40°F~1832°F)
6000	Display Counts	6000
Φ28mm	Jaw Opening	Φ28mm
P	Auto Range	P
True RMS	True RMS	True RMS
P	Connuity/Diode	P
P	NCV (Red LED Flashing)	P
P	AC Live	P
P	Auto power off	P
P	Max/Min	P
P	Zero/Rel	P
P	Backlight/Torch	-

GUANGZHOU ZHENGNENG ELECTRONIC TECHNOLOGY CO., LTD.

FUZRR®

MAKE THE BEST TESTING INSTRUMENT!

Why choose us!



VS



FR204E		204+
60.00A/600A	DC Current (A)	60.00A/600A
60.00A/600A	AC Current (A)	60.00A/600A
600mV/6V/60V/600V	DC Voltage (V)	600mV/6V/60V/600V
6V/60V/600V	AC Voltage (V)	6V/60V/600V
6V/60V/600V	LowZ AC Voltage (V)	-
1kHz	ACV/Bandwidth (Hz)	400Hz
10Hz~60kHz	Frequency (ACV Hz)	10Hz~60kHz
600Ω/6KΩ/60KΩ/600KΩ 6MΩ/60MΩ	Resistance (Ω)	600Ω/6KΩ/60KΩ/600KΩ 6MΩ/60MΩ
60nF~600n~600uF 6000uF/60000uF	Capacitance(F)	60nF~600n~600uF 6000uF/60000uF
(-50°C~1000°C)	Temperature (℃)	(-40°C~1000°C)
(-58°F~1832°F)	Temperature (°F)	(-40°F~1832°F)
6000	Display Counts	6000
Φ28mm	Jaw Opening	Φ28mm
P	Auto Range	P
True RMS	True RMS	True RMS
P	Connuity/Diode	P
P	NCV (Red LED Flashing)	P
P	AC Live	P
P	Auto power off	P
P	Max/Min	P
P	Zero/Rel	P
P	Backlight/Torch	-

GUANGZHOU ZHENGNENG ELECTRONIC TECHNOLOGY CO., LTD.

Model Selection

Function / Model	FR203E	FR204E	Accuracy
DC Current (A)	40A / 400A	60A / 600A	±(2%+5)
AC Current (A)	40A / 400A	60A / 600A	±(2%+5)
DC Voltage (V)	600V	600V	±(0.5%+3)
AC Voltage (V)	600V	600V	±(0.8%+3)
LowZ AC Voltage (V)	-	600V	±(1.5%+5)
ACV / Bandwidth (Hz)	400Hz	1kHz	-
ACA / Bandwidth (Hz)	60Hz	60Hz	-
Frequency (ACV Hz)	40kHz	60kHz	±(0.5%+5)
Resistance(Ω)	400Ω~400kΩ 4MΩ~40MΩ	600Ω~600kΩ 6MΩ~60MΩ	±(1%+5) ±(2%+5)
Capacitance (F)	40nF / 400uF 40000uF	60nF / 600uF 60mF	±(4%+5) ±(8%+5)
Temperature (°C)	-	(-50°C~1000°C)	±(1.5%+4)
Temperature(°F)	-	(-58°F~ 1832°F)	±(2%+5)
FEATURES			
Display Counts	4000	6000	
ACV LowZ	-	●	
Jaw Opening	Φ28mm		
Auto Range	●		
True RMS	●		
Connuity / Diode	●		
Auto power off	●		
Backlight / Torch	●		
Battery	AAA1.5V×2		
Category Ratings	CAT III 300V CAT II 600V		

Function Description

Instrument Structure



Overall Dimensions



Product Accessories

FR204E













FR203E













